

MAGNETIC TORQUE TRANSFER DEVICE
CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application claims priority to United States Provisional Patent Application No. 60/493,551 filed August 11, 2003, which application is
5 herein expressly incorporated by reference.

FIELD OF THE INVENTION

[0002] The present invention generally pertains to motor vehicles. More particularly, the present invention pertains to a magneto rheological fluid based torque transfer device.

10 **BACKGROUND OF THE INVENTION**

[0003] There has been great interest in the use of magneto rheological fluid (MRF) technology for the development of products in recent years, including, but not limited to, the automotive industry. MRF is a fluid that contains minute particles of iron in a carrier fluid. The MRF approaches a
15 solid when subjected to a magneto field. Much of the interest in the automotive industry had been related to clutches and brakes.

[0004] While known MRF based torque transfer devices have attracted a significant amount of interest, they are all associated with known drawbacks. These drawbacks include, but are not limited to, low torque
20 capability relative to other technologies, separation of the iron particles from the carrier fluid when the device is rotated at high speed, parasitic drag losses, and high cost for a specific torque capability as compared to other technology.

[0005] Accordingly, a need remains in the pertinent art for an MRF
25 based torque transfer device that overcomes the limitations associated with the prior art.

SUMMARY OF THE PRESENT INVENTION

[0006] It is a general object of the present invention to provide a new and improved assembly that overcomes the previously delineated
30 drawbacks of conventional MRF based torque transfer devices.

[0007] It is another object of the present invention to provide an improved torque transfer device, such as a clutch or a brake, that transmits torque equal to or exceeding other conventional technology of equivalent size.

[0008] It is a further object of the present invention to provide a torque transfer device, such as a clutch or a brake, that has faster and more accurate response as compared to conventional technology.

5 [0009] It is yet another object of the present invention to provide a torque transfer device, such as a clutch or a brake, that is less expensive to manufacture than a clutch or brake that uses conventional technology.

[0010] In one form, the present invention provides a magnetic torque transfer device. The magnetic torque transfer device includes an input member and an output member. The input member rotatably drives at least
10 one input gear. The output member drives at least one output gear. The at least one input gear has a first plurality of gear teeth meshingly engaged with a second plurality of gear teeth of the at least one output gear. A magneto rheological fluid is disposed between at least some of the meshing first and second pluralities of gear teeth.

15 [0011] In another form, the present invention provides a torque assembly including an input assembly and an output assembly. A magneto rheological fluid (MRF) is disposed between the input and output assemblies. The MRF is operative in a first state for permitting relative rotation between the input and output assemblies and in a second state for coupling the input
20 and output assemblies for common rotation. In the second state, the MRF operates in a compression mode.

[0012] In another form, the present invention provides a method of transferring torque from an input shaft to an output shaft. The method includes the step of providing a device having an input assembly coupled for
25 relative rotation to an output assembly. The device further has a magneto rheological fluid (MRF) disposed between the input and output assemblies. The method further includes the step of activating the MRF to couple the input shaft for common rotation with the output shaft in a compression mode.

[0013] Further areas of applicability of the present invention will
30 become apparent from the detailed description provided hereinafter. It should be understood that the detailed description and specific examples, while indicating the preferred embodiment of the invention, are intended for purposes of illustration only and are not intended to limit the scope of the invention.

[0014] Additional benefits and advantages of the present invention will become apparent to those skilled in the art to which this invention relates from a reading of the subsequent description of the preferred embodiment and the appended claims, taken in conjunction with the accompanying
5 drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0015] The present invention will become more fully understood from the detailed description and the accompanying drawings, wherein:

[0016] Figure 1 is a cross-sectional view illustrating an MRF based
10 torque transfer application of the prior art.

[0017] Figure 2A is a side view of a clutch constructed in accordance with the teachings of the present invention.

[0018] Figure 2B is an end view of the clutch of Figure 2A.

[0019] Figure 3 is cross-sectional view taken along the line 3-3 of
15 Figure 1.

[0020] Figure 4 is cross-sectional taken along the line 4-4 of Figure 1.

[0021] Figure 5 is an enlarged view of pinion shaft seals.

[0022] Figure 6A is a side view illustrating a brake constructed in
20 accordance with the teachings of the present invention.

[0023] Figure 6B is an end view of the brake of Figure 6A.

DETAILED DESCRIPTION

[0024] The following detailed description is merely exemplary in nature and is in no way intended to limit the present invention, its application,
25 or uses.

[0025] Before addressing the present invention, a brief understanding of the current state of the art is warranted. With initial reference to Figure 1, illustrated is a cross-sectional view of a portion of a conventional MRF clutch A. The clutch A generally includes an input element
30 B and an output element C. An MR fluid D is radially disposed between the input and output elements B and C. Assuming the input element B is rotating faster than the output element C, when the MR fluid D is subjected to a magneto field by an actuating coil, it becomes nearly a solid. There is effectively no clearance between input element B and the MR fluid D and

there is effectively no clearance between the MR fluid D and output element C. Torque is transmitted through the shearing of the magneto flux between the input and output elements B and C and the MR fluid D when the actuating coil is energized. Separation of the iron particles can be a problem if the assembly is rotated at high speed for a long time. Transmitted parasitic torque (*i.e.*, drag) when the actuating coil is not energized can also be a problem in some applications.

[0026] Turning to Figures 2A, 2B and 3 through 5, a clutch constructed in accordance with the teachings of the present invention is illustrated and generally identified at reference character 10. The clutch 10 is generally illustrated to include an input member 12 and an output member 13. As will become more apparent below, the input member 12 and the output member 13 are normally permitted to rotate relative to one another.

[0027] With particular reference to the cross-sectional view of Figure 3, the input member 12 is illustrated to include an input shaft 12A integral with an input driver 30. The driver 30 has four bored holes at 90 degrees apart for bushings 25. The bushings 25 support one end of pinion shafts 24. A space 49 between the ends of the pinion shafts 24 and the input driver 30 and end flange 32 is filled with grease for permanent lubrication of the bushings 25. The end flange 32 has identical bored holes as the input driver 30 for bushings 25 to support the opposite end of the pinion shafts 24. Each pinion shaft 24 has involute teeth as shown particularly in Figure 4. These teeth mesh with the internal teeth of the cylindrical extension 20 of the driven flange 18 with a backlash (clearance) of approximately one-half millimeter (0.20"). The grooves 23 are provided in the extension 20 for proper control of the electrical flux field.

[0028] The input member 12 further includes an intermediate member or spacer 33. The spacer 33 is coupled for rotation with the input shaft 12 and may be constructed of aluminum or other non-magneto material. The spacer 33 has an integral flange 48 on one end for attachment to the input driver 30 with appropriate dowels and screws. The shape of the spacer 33 other than the flange 48 is shown particularly in Figure 4.

[0029] The flange attaches to the spacer 33 and the bushing housing 32 attaches to the flange 31. The input assembly is supported on the

input end by a sealed bearing 35 and by a sealed bearing 28 on the opposite end. A retaining ring 36 keeps the bearing 35 in its correct position and a retaining ring 47 keeps the bearing 28 in its correct position. The input end housing 15 mounts to a coil housing 17 and supports the sealed bearing 35.

- 5 The output shaft 13 may be integral with the output housing 19 and has cylindrical extension 50 to mount the sealed bearing 28.

[0030] The torque transfer device 10 is further illustrated to include means for activating the MRF. The means for activating may include one or more electrical coils 21 mount on the outside of the cylindrical extension 20.

10 The cylindrical extensions separate the electrical coils 21 from the MR fluid. The coil housing 17 contains the coils 21 and provides the necessary flux path. O-rings 22 seal the assembly against any leakage of the MRF.

[0031] A slip ring 41 is attached to the input end housing 15 and retains the sealed bearing 35. The slip ring 41 incorporates bronze bushings 43 that are in contact with brushes 38. Springs urge the brushes 38 against the bushings 43 to maintain good electrical contact. A slip ring housing 37 is stationary and supported on the slip ring 31 by a sealed bearing 44. The slip ring housing 37 is split at one centerline and held together by screws 48. A cover 40 retains the springs 38 and provides access of the electrical leads to

15 20 the assembly.

[0032] Figure 4 is a cross-sectional view taken along the line 4-4 of Figure 1. As stated above, the spacer 33 may be constructed of non-magneto material. Pole pieces 51 are steel for magneto flux path control and are attached to the spacer 33 by screws 52. The assembly is filled with MRF such the fluid fills the angular space between the cylindrical extension 20 and surfaces 53 of the pole pieces 51.

25

[0033] With reference to Figure 5, an enlarged view of the pinion shaft seals is provided. Element 27 is tight fit in a flange 48 due to the nature and design of piston rings 27. Surfaces 49 in the pinion shaft 24 form a close clearance fit with the piston ring 27. In operation, the piston ring 27 is rotationally fixed relative to the flange 48. This construction makes an effective seal against the ingress of MRF to the seal 26. This is important because this fluid causes premature wear with contact to the sealing lip of the seal 26. The seal 26 is a commercially available seal that can withstand

30

pressures up to 25 bar which is much higher than the pressure of the grease used for lubrication of the bushing 25 due to centrifugal force. The piston rings 29 and 34 provide seals against the ingress of MR fluid to the sealed all bearings 28 and 36.

5 **[0034]** Figure 6 illustrates, in exemplary form, the teachings of the present invention incorporated into a brake assembly 200. Element 212 is the input shaft of the brake assembly 200 and can be splined as shown or have keyways. Elements 215,216,217,218 and 219 are stationary. It will be understood that the internal components of the brake assembly are the same
10 as described above relative to the clutch assembly 10 except that no slip ring assembly is required.

OPERATION

[0035] Particular reference will again be made to Figure 4 for purposes of describing the operation of the clutch assembly 10. Those skilled
15 in the art will realize that the brake assembly 100 is similarly operated. Assume the rotation of the spacer 33 which is connected to the input shaft 12 is as shown by arrow 33. If the coils 21 are not energized, the pinion shafts 24 rotate in the direction of arrow 61 and the coils 21 and the coil cover 17 that are connected to the output shaft 13 do not rotate. The vast majority of
20 the MRF circulates within the unit as shown by arrow 63. The small amount of MR fluid 64 will pass through the meshes of the pinion shaft 24 teeth and the teeth in the cylinder extension 20 because of the large backlash (clearance) between them and be directed to the grooves 23 in the cylindrical extension 20. This rotation of the pinion shafts 24 keeps the iron particles in
25 the MRF mixed with the carrier fluid.

[0036] Parasitic drag losses of the clutch assembly 10 are very low compared to MRF clutches using conventional application technology. One reason for this is the small physical size of the present invention compared to conventional application technology. The second reason is that a small
30 portion of the total surface areas has a small gap between adjacent moving parts. As known by those skilled in the art, parasitic losses between adjacent moving surface are inversely proportional to the square of the gap distance.

[0037] When the coils are fully energized, MRF 64 approaches a solid and blocks the revolution of teeth of pinion shafts 24. This causes the

cylindrical extension 20, and thus the output shaft 13, to rotate in the same direction and at the same speed as the input shaft 12A when the output load is equal or less than the torque rating of the clutch assembly 10. For some applications, such a vehicle torque management of power from the transmission of the rear wheels, high-speed engagement is essential for proper performance. The teachings of the present invention can transmit full rated torque in as little as 50 milliseconds for a clutch with a torque of 1500 Nm. The torque capability of the present invention is 25 or more times the torque capability of a clutch of the same dimensions using conventional MRF application technology. By way of example, a clutch with a torque capacity of 1500 Nm (1106 lbs-ft) is 160 millimeters (6.29 inches) in diameter and 200 millimeters (7.87 inches) long.

[0038] Soft engagement of the present invention may occasionally be required such as its application as the vehicle's main clutch that is mounted between the engine and the transmission. This soft engagement is accomplished by modulating or gradually increasing the current applied to the coils 21 to the current required to transmit the desired torque. The torque required when the present invention is used as the vehicle's main clutch can be for example 550 Nm (405 lbs-ft). The size of the present invention is much smaller than the conventional dry-friction clutch.

[0039] The description of the invention is merely exemplary in nature and, thus, variations that do not depart from the gist of the invention are intended to be within the scope of the invention. In this regard, it is to be understood that the invention is not to be limited to the exact construction and/or method that has been illustrated and is discussed above. Such variations are not to be regarded as a departure from the spirit and scope of the invention.